HEPA 650W POWER STORAGE UNIT





Lithium Iron Phosphate Power System safe, durable, efficient and environmentally friendly



15W Wireless Charging For Mobile Devices



Elegant, Compact Design, High Quality Finish



Sturdy construction, with internal reinforcement bracket for added safety



LED reading light (On Handle)



High Quality LCD Display Showing All Functions At A Glance



Affordable













*Not limited to the above specifications plug, for other specifications please contact sales to order.



HEPA 650W POWER STORAGE UNIT

OVERVIEW	

 Weight
 15.50 lb / 7 kg

 Dimensions
 10 x 10 x 6 in / 250 x 250 x 155mm

 Power Capacity
 608Wh

DETAILS

Package Dimensions

Cell	LFP (LiFePO4) Lithium – Iron Phosphate
Cycles	≥3000
Operating temp.	14 F to 140 F / -10°C bis 60°C
Charging temp.	32 F to 113 F / 0°C bis 45°C
Protective Functions	over charge/over discharge/over current/over temp/ short circuit/over voltage

14 x 12 x 10 in / 360 x 300 x 245mm

OUTPUT

AC output (x2)	110V, 60Hz / 220V, 50Hz / Continuous Power 650W / Peak Power 1200W
AC rated power capacity	547Wh
DC output	12V - 10A
USB output	5V-2A/QC3.0-18W
USB Support Protocol	FCP/QC3.0/QC2.0/Apple mode/AFC/BC1.2
Wireless Charging	Max 15W
Wireless Charging Protocol	WPC1.2.4 EPP

INPUT (CHARGING

USB C-PORT	Use a PD charger with the regular USB-C cable for quick charge
TYPE-C	5V/9V/12V/15V/20V/3A/5A
TYPE-C Support Protocol	PD2.0/PD3.0/QC2.0/QC3.0/QC3+/FCP/AFC/SCP/Apple
AC Adapter	20V-3.5A Max 5A/100W Adapter
DC from PV Panel	60V-10A (Max 200W)

CERTIFICATIONS

PSE/IEC62133 Report/METI filing/UN38.3/MSDS/ROHS/CE/EMC/LVD/FCC/ Sea and air freight certificate / Drop test Report

ACCESSORIES

Car charger cable/AC adapter/AC charger cable/ PV adapter cable/Product Manual/Certificate/Warranty Card